



SITEF GRADE 2

TEFLON[®] BASED SILICONE GREASE

DESCRIPTION

SITEF GRADE 2 is a high performance silicone grease based on finely divided Teflon[®] additives, formulated for the lubrication of equipments subjected to acid or alkaline contamination.

SITEF GRADE 2 is particularly recommended for mechanisms operating at low speed under extreme high or low temperatures.

APPLICATIONS

- Articulated joints, linear bearings, ball bearings, pneumatic mechanisms and jacks running at low speed under extreme high or low temperatures:
 - Industrial Bakeries
 - Food processing Industry
 - Beverage manufacturing industry
 - Aircraft industry
 - Refrigeration industry
- Assembly and greasing under vacuum conditions of water fittings, valves and taps:
 - Refrigeration industry
 - Chemical industry
 - Petrochemical industry
- Lubrication of elastomers and polymers as well as metal to rubber contacts:
 - Automotive Industry
 - Aircraft Industry
 - Etc.

PRODUCT BENEFITS

- High stability under wide temperature range: - 60°C to + 280°C.
- Good resistance to acid, alkaline and solvent contamination.
- Excellent resistant to water washout.
- Low coefficient of friction on metallic, plastic and elastomer materials.
- Good performance to extreme pressure frictions.
- Non staining; colourless.
- Suitable for hygienic atmosphere of food and pharmaceutical facilities.
- Non Toxic.
- Reduces maintenance spare parts costs.
- Extends lubrication intervals and reduces labour costs and downtime.

APPROVALS

- Approved InS H1 (Reg N° 1795184) for incidental food contact for use in and around food processing areas in locations in which there is a potential exposure of the lubricated part to food.
- CNERNA 1992
- Approved n1 by the Canadian Food Agency (CFIA).
- Meets the requirement of AIRBUS Industry: PQ 81600.



PHYSICAL PROPERTIES

Colour:	White
Appearance.....	Paste
Base Oil.....	Silicone
Thickener	Inorganic
NLGI grade.....	2
Penetration after 60 strokes	265 / 295
Solidification Point.....	- 60°C
Drop point (NFT 60-102)	None
Operating temperature range	- 60°C to + 280°C
Maxi evaporation rate (24 hrs @ 200°C).....	2%

DIRECTIONS FOR USE

SITEF GRADE 2 is not compatible with mineral greases. Complete purging and cleaning is essential before application.
SITEF GRADE 2 can be removed with solvents.
Apply grease evenly in thin layers to surfaces.

STORAGE & SAFETY

Three years, stored in closed original packaging at ambient temperature.
Bulk: Under normal condition of use, no specific hazard.

For further information, please consult the Materials Safety Data Sheet.

PACKAGING

Tin 1kg x 6

(Ref. O-0620-B7)

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992

Tel: +65 6265 2888 | Fax: +65 6268 6474

Website: www.orapiasia.com



TDS 620 / 004 – 28/04/2023

2/2

The ORAPI Group designs, manufactures and markets " Highly Technical Solutions" for Maintenance Repair and overhaul of machines and equipments. The Group is present in over 100 countries with 32 subsidiaries and an international network of import-distributors. The Group operates 7 manufacturing plants and 4 laboratories of R&D. ORAPI is certified ISO 9001 and ISO 14001.