



# ORAMETAL POCKET

## UNIVERSAL PUTTY WITH STEEL PARTICLES

### DESCRIPTION

Pre-dosed, mouldable epoxy putty for repairing all materials, especially metals.

### APPLICATIONS

- Maintenance and repair in mechanics, wood-working and other applications.
- Sealing. Restoring and sealing leaks in piping.
- Use in gas and water tanks, radiators, sanitary or electric installations, pools, etc.
- Repairing pipes, faucets, drains, pumps, etc.
- Repairing tools, banisters, damaged threads, bodies of appliances, window frames, doors, etc.
- Ideal for all quick repair jobs.
- Must-have product in your toolbox.

### PRODUCT BENEFITS

- No waste; use only the amount required.
- Provides good bond on all materials, such as metals, PVC, wood, etc.
- Excellent resistance to oils, hydrocarbons, hot and cold water, acids and bases, alcohol, etc. very well.
- Possesses excellent, long-lasting stability. Does not rust.
- After complete drying, can be drilled, tapped, machined and painted.

### PHYSICAL PROPERTIES

Aspect .....	Paste
Colour .....	Grey
Operating temperature .....	-40°C to +150°C
Hardness .....	80 Shore D
Useful life of mixed paste .....	<5 minutes
Complete drying time .....	30 minutes
Compression strength .....	84 N/mm <sup>2</sup>
Tensile strength .....	20 N/mm <sup>2</sup>
Complete drying .....	24 hours
Compression strength .....	84 MN/m <sup>2</sup> (12,000 psi)
VOC content .....	0%
Dielectric strength .....	400 Volts / mil
Electrical resistance	30,000 megaohms

## DIRECTIONS FOR USE

---

We recommend that you wear gloves while handling this product.  
Cut off the amount of product you need for making the repair.  
Knead for 1 minute until you obtain a homogenous paste.  
Apply to clean and dry surface within 3 minutes of mixing the paste.  
Application temperature: +5°C to +40°C.  
For emergency repairs, paste can be used on wet and submerged surfaces.  
However, we recommend you apply the putty on clean and dry surfaces.

## STORAGE

---

Two years, stored in closed original packaging in a cool and dry environment.

## PACKAGING

---

125 g stick                      Ref. O 221 D1                      x 12

## WARRANTY

---

*The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.*